
Three-Dimensional Imaging with Atomic Resolution in Phase TEM

Migrating Nano-Science Toward Nanotechnology of Energy Saving Windows and E-paper

Fu-Rong Chen

Dept. of Engineering and System Science National Tsing Hua University Hsin Chu, Taiwan

奈米物理特論,物理館019教室,12/24/2009



Better electron microscopes

NTHU

It would be very easy to make an analysis of any complicated chemical substance; all one would have to do would be to look at it and see where the atoms are.

The only trouble is that the electron microscope is one hundred times too poor.

Develop new tool to discover new science!

-Richard F. Feynman

-12.29.1959 American Physics Society, CIT

My talk will cover

(a) Toward atomic resolution tomography (Dirk Van Dyck and Christian Kisielowski)

(b) Development of "phase (plate)/ wet cell TEM"

(c) Migration from nano-science toward nanotechnology: Smart Window for Energy Saving and e-paper

My talk will cover

- (a) Toward atomic resolution tomography (Dirk Van Dyck and Christian Kisielowski)
- (b) Development of "phase (plate)/ wet cell TEM"
 - -- for advanced nano-biological imaging
 - (c) Migration from nano-science toward nanotechnology: Smart Window for Energy Saving and e-paper

My talk will cover


- (a) Toward atomic resolution tomography (Dirk Van Dyck and Christian Kisielowski)
- (b) Development of "phase (plate)/ wet cell TEM"
 - -- for advanced nano-biological imaging
 - (c) Migration from nano-science toward nanotechnology: Smart Window for Energy Saving and e-paper
 - scaling up the nano-materials



Particle-Wave Duality




Particle-Wave Duality







Particle-Wave Duality





Particle-Wave Duality









Particle-Wave Duality

NTHU





Amplitude

Phase




Phase Difference






Particle-Wave Duality


NTHU



Amplitude

Phase







$$I=\psi\psi^*=|A|^2$$






(a) Toward atomic resolution tomography







Dynamics scattering exit wave Ψ=Aexp(-iφ)




Dynamics scattering exit wave Ψ=Aexp(-iφ)






Dynamics scattering exit wave Ψ=Aexp(-iφ)





Lens Aberration

phase plate


$$\chi = \pi \lambda \Delta f g^2 + \frac{\pi}{2} C_s \lambda^3 g^4$$








Dynamics scattering exit wave Ψ=Aexp(-iφ)





Dynamics scattering exit wave Ψ=Aexp(-iφ)

1. Atomic structure is heavily encoded in images

Little information about composition and thickness(


 Δf_1


2-D projection

Phase Lost I(g)Fourier **Transform** (linear Image) Δf_2 Phase Lost I(r)



phase plate $\chi = \pi \lambda \Delta f g^2 + \frac{\pi}{2} C_s \lambda^3 g^4$





Dynamics scattering exit wave Ψ=Aexp(-iφ)


1. Atomic structure is heavily encoded in images


Little information about composition and thickness(


 Δf_1


2-D projection

Phase Lost I(g)Fourier **Transform** (linear Image) Δf_2 Phase Lost I(r)











Dynamics scattering exit wave Ψ=Aexp(-iφ)





NTHU



object 1

Diffraction Plane


image 1



Object 2



NTHU






object 1

Diffraction Plane

image 1






Object 2










object 1




Diffraction Plane






Object 2




FFT







object 1




FFT

FFT

Diffraction Plane




Object 2




NTHU

image 1






object 1




FFT

FFT

Diffraction Plane



FFT-1



FFT⁻¹


image 2

image 1


NTHU

Object 2







object 1



Diffraction Plane





FFT

FFT⁻¹

FFT⁻¹





image 1



image 2




Object 2





(TIE non-interference method) (medium resolution ~ 100 nm)

objective lens Back Focal image plane sample
Plane




(TIE non-interference method) (medium resolution ~ 100 nm)







(TIE non-interference method) (medium resolution ~ 100 nm)


NTHU







(TIE non-interference method) (medium resolution ~ 100 nm)





(TIE non-interference method) (medium resolution ~ 100 nm)





 $\Delta f = 0$


12

TIE: The phase is encoded in the "Gradient" of Image intensity

Phase Lost



(TIE non-interference method) (medium resolution ~ 100 nm)




$$\nabla_{\perp} \bullet (I(r_{\perp},0) \nabla_{\perp} \phi) = -k \partial_{z} I(r_{\perp},z)$$



Transport Intensity Equation

(TIE non-interference method) (medium resolution ~ 100 nm)



TIE: The phase is encoded in the "Gradient" of Image intensity


$$\nabla_{\perp} \bullet (\mathsf{I}(\mathsf{r}_{\perp},0)) \nabla_{\perp} \varphi) = -\mathsf{k} \partial_{z} \mathsf{I}(\mathsf{r}_{\perp},z) \qquad \underbrace{I_{3} - I_{1}}_{\Delta f_{3} - \Delta f_{1}}$$

Two de-focus images

TEM CENTER

Transport Intensity Equation

(TIE non-interference method) (medium resolution ~ 100 nm)




TIE: The phase is encoded in the "Gradient" of Image intensity

$$\nabla_{\perp} \bullet (((r_{\perp}, 0)) \nabla_{\perp} \phi) = -k \partial_{z} I(r_{\perp}, z)$$
in-focus image
$$I_{3} - I_{1}$$
Two de-focus images
$$I_{2}$$

TEM CENTER

Transport Intensity Equation

(TIE non-interference method) (medium resolution ~ 100 nm)




TIE: The phase is encoded in the "Gradient" of Image intensity


$$\nabla_{\perp} \bullet (((\mathbf{r}_{\perp}, \mathbf{0})) \nabla_{\perp} \phi) = -\mathbf{k} \partial_{\mathbf{z}} \mathbf{l}(\mathbf{r}_{\perp}, \mathbf{z})$$
in-focus image
$$\mathbf{l}_{2} \qquad (\mathbf{r}_{\perp}, \mathbf{z}) \text{ is phase}$$


$$\mathbf{k} = 2\pi / \lambda \text{ wave vector}$$


$$\mathbf{l}_{2} \qquad \mathbf{l}_{3} - \mathbf{l}_{1}$$
Two de-focus images










































$$\nabla_{\perp} \bullet (\mathsf{I}(\mathsf{r}_{\perp},0) \nabla_{\perp} \varphi) = -\mathsf{k} \partial_{\mathsf{z}} \mathsf{I}(\mathsf{r}_{\perp},\mathsf{z})$$















retrieved phase at exit surface


$$\nabla_{\perp} \bullet (I(r_{\perp},0) \nabla_{\perp} \phi) = -k \partial_{z} I(r_{\perp},z)$$













retrieved phase at exit surface

$$\nabla_{\perp} \bullet (\mathsf{I}(\mathsf{r}_{\perp},0) \ \nabla_{\perp} \varphi) = -\mathsf{k} \partial_{\mathsf{z}} \mathsf{I}(\mathsf{r}_{\perp},\mathsf{z})$$


$$\phi(x,y) = C_E \int V(x,y) dz + \frac{e}{h} \int \overline{B(x,y)} dA dz - \frac{\pi}{\lambda E_o \varepsilon} \int \overline{P(x,y)} dr dZ$$






modulus at exit surface


$$\nabla_{\perp} \bullet (I(r_{\perp}, 0) \nabla$$




retrieved phase at



$$\phi(x,y) = C_E \int V(x,y)dz + \frac{e}{h} \int \overline{B(x,y)}dAdz - \frac{\pi}{\lambda E_o \varepsilon} \int \overline{P(x,y)}drdZ$$






modulus at exit surface


$$\nabla_{\perp} \bullet (I(r_{\perp}, 0) \nabla_{\perp})$$

$$\Delta V_{pn} = \frac{\Delta \varphi}{C_E t} = 0.91V$$

$$\phi(x,y) = C_E \int V(x,y) dz + \frac{e}{h} \int \overline{B(x,y)} dA dz - \frac{\pi}{\lambda E_o \varepsilon} \int \overline{P(x,y)} dr dZ$$




retrieved phase at







Equi-Potential Map around Nano-Tip












Transport of Intensity Equation





simulated P(x,y)







Equi-Potential Map around Nano-Tip


$$\phi(x,y) = C_E \int V(x,y) dz - \frac{e}{h} \int \overrightarrow{B(x,y)} dA dz \left(\frac{\pi}{\lambda E_o \varepsilon} \int \overrightarrow{P(x,y)} dr dZ \right)$$















Reconstructed Exit Wave of Ge

- from de-focal series of Cs corrected HRTEM images

 $\begin{array}{ll} C_s = 0.003 mm & \Delta f = 0 nm \\ \delta f = 2 nm & \\ \alpha = 0.15 mrad & step = -2 nm \\ C_s 5 = 5 mm & 35 images \end{array}$




de-focal series Images contribute from Christian Kisielowski, NCEM, Berkeley

Reconstructed Exit Wave of Ge

- from de-focal series of Cs corrected HRTEM images

 C_s =0.003mm Δf =0nm δf =2nm α =0.15mrad step=-2nm C_s 5=5mm 35 images



de-focal series Images contribute from Christian Kisielowski, NCEM, Berkeley


Propagation of Electron Wave inside Crystal (Channeling, 1s state wave)

MCENTEArgand Plot for Exit Wave Au **UHU** modulus phase Au Si 1.5 2 Au Im(EW) 1 Au 60nm thickness -1.5Re(EW)

Re(
$$\psi(r,z)-1$$
) = $-2C_{1s}\sin^2(\pi \frac{E_{1s}}{E_0}\frac{k}{2}z)\phi_{1s}$

$$\operatorname{Im}(\psi(r,z)-1) = -2C_{1s}\sin(\pi \frac{E_{1s}}{E_0} \frac{k}{2} z)\cos(\pi \frac{E_{1s}}{E_0} \frac{k}{2} z)\phi_{1s}$$

Propagation of Electron Wave inside Crystal (Channeling, 1s state wave)



$$\operatorname{Re}(\psi(r,z)-1) = -2C_{1s}\sin^{2}(\pi \frac{E_{1s}}{E_{0}} \frac{k}{2}z)\phi_{1s}$$

$$\operatorname{Im}(\psi(r,z)-1) = -2C_{1s}\sin(\pi \frac{E_{1s}}{E_{0}} \frac{k}{2}z)\cos(\pi \frac{E_{1s}}{E_{0}} \frac{k}{2}z)\phi_{1s}$$

Atomic column acts as "positive" electro-static lens





White atomic column





Black atomic column




























20Å Au


99999999999999999999999999999999999 9999999999999999999 99 99 99 99 99 99 99 99 99 999999999999 99 99 99 99 99 99999


99999999999999999999999999999999999 99999999999999999 99 99 99 99 99 99 99 99 99 99 9999999999999 00 00 00 00 00 99999


Plane of Reconstructed EW














































flat top wedge




1441 atomic columns

flat bottom wedge

```
20Å
```




flat top wedge




Plane of Reconstructed EW


1441 atomic columns

flat bottom wedge





flat top wedge




Plane of Reconstructed EW


1441 atomic columns

flat bottom wedge


20Å




Au Wedge Crystal




Au Wedge Crystal






Focus Corrected EW

NTHU




modulus of as reconstructed EW

modulus of focus corrected EW




Focus Corrected EW

NTHU




modulus of as reconstructed EW


modulus of focus corrected EW





Exit wave reconstruction













NTHU



NTHU




TEM CENTER

From Exit wave to Structure Reverse Multislice Method


NTHU

$$q_o(x,y)=exp\{iC_EV(x,y)c\}$$




Reverse Multislice Method

$$q_o(x,y)=exp\{iC_EV(x,y)c\}$$



specimen can be subdivided into thin slices of phase grating


$$q_o(x,y)=exp\{iC_EV(x,y)c\}$$



 $(\Psi_0 \cdot q_o(x,y))$

specimen can be subdivided into thin slices of phase grating


$$q_o(x,y)=exp\{iC_EV(x,y)c\}$$



 $(\Psi_{o} \cdot q_{o}(x,y)) \otimes p(x,y)]$


specimen can be subdivided into thin slices of phase grating

$$q_o(x,y)=exp\{iC_EV(x,y)c\}$$



 $(\Psi_{o}\cdot q_{o}(x,y))\otimes p(x,y)]q_{o}(x,y)$

$$q_o(x,y)=exp\{iC_EV(x,y)c\}$$




$$(\Psi_{o} \cdot q_{o}(x,y)) \otimes p(x,y)] q_{o}(x,y) \dots) q_{o}$$

specimen can be subdivided into thin slices of

$$q_o(x,y)=\exp\{iC_EV(x,y)c\}$$


phase grating



$$(\Psi_{o} \cdot q_{o}(x,y)) \otimes p(x,y) q_{o}(x,y) \dots q_{o}(x,y) - \Psi_{e}$$

Reverse Multislice Method

$$q_o(x,y)=exp\{iC_EV(x,y)c\}$$




$$\chi^{2} = \{ (\Psi_{0} \cdot q_{o}(x,y)) \otimes p(x,y)] q_{o}(x,y) \dots) q_{o}(x,y) - \Psi_{e} \}^{2}$$

Reverse Multislice Method

$$q_o(x,y)=exp\{iC_EV(x,y)c\}$$

$$\partial \chi^2 / \partial V(x,y) = 0$$



$$\chi^2 = \{ (\Psi_0 \cdot q_o(x,y)) \otimes p(x,y) | q_o(x,y) \dots q_o(x,y) - \Psi_e \}^2$$


Reverse Multislice Method

specimen can be subdivided into thin slices of phase grating

$$q_o(x,y)=exp\{iC_EV(x,y)c\}$$


$$\partial \chi^2 / \partial V(x,y) = 0$$

Potential Map




$$\chi^{2} = \{ (\Psi_{0} \cdot q_{o}(x,y)) \otimes p(x,y)] q_{o}(x,y) \dots) q_{o}(x,y) - \Psi_{e} \}^{2}$$

Analysis of EW Atomic Column by column





 χ^2 map vs iterations and number of slices for input EW

21



Segregation of Cu in Σ5 Grain Boundary in Al





	EXP	Retrived
X _{cu}	1%	0.8%

$$V_o = x_{AI} V_{o,AI} + x_{cu} V_{o,Cu}$$

$$V_o(x,y)=X_{Al}(x,y)V_{o,Al}+X_{Cu}(x,y)V_{o,Cu}$$

$$X_{Al}(x,y) = \frac{V_{o,Cu} - V_{o}(x,y)}{V_{o,Cu} - V_{o,Al}}$$


$$V_{o, Cu} = 23.5 eV, V_{o, Al} = 17 eV$$

$$X_{Cu}(x,y) = \frac{V_{o}(x,y) - V_{o,Al}}{V_{o,Cu} - V_{o,Al}}$$

$$V_{o}(x,y)$$

$$X_{Al}(x,y)*t(x,y)$$

$$X_{Cu}(x,y)*t(x,y)$$



	EXP	Retrived
X _{cu}	1%	0.8%

Fu-Rong Chen, Christian Kisielowski, Joerg R. Jinschek



Bonding Energy of Al Grain Boundary to Cu Solute

NTHU

$$X_{cu}exp(Q/kT)$$

$$X_{cu}b = \frac{X_{cu}exp(Q/kT)}{(1-X_{cu})+X_{cu}exp(Q/kT)}$$

X_{cu}^b: the concentration of Cu at grain boundary

X_{cu}: the concentration of Cu in matrix

Q: the bonding energy of grain boundary to solute atom Cu

T: temperature

Calculated Q =0.02eV/atom

Conclusions

- Focal plate: determination of the geometry of exit surface of sample
- Correction of dynamic scattering is an important issue for quantification of the structure (Reverse multislice or 1s state model)
- For sample containing single element, it is possible to reconstruct 3-d structure with focal series images... Au wedge case

We are working on the REWs from experimental cases

• (b) Development of "phase (plate)/ wet cell TEM"





Wet cell


NTHU

Phase Plate

MEMs fabrication

Bottlenecks for Biological Imaging






Phase Plate

MEMs fabrication

Bottlenecks for Biological Imaging






Phase Plate

MEMs fabrication

Bottlenecks for Biological Imaging

a) Lack of contrast:





Phase Plate


MEMs fabrication

Bottlenecks for Biological Imaging

a) Lack of contrast:

b) Only dry sample is allowed:





Phase Plate


MEMs fabrication

Bottlenecks for Biological Imaging

- a) Lack of contrast: Zernike Phase Plate

 (alternate the phase of electron wave in focal plane)
- b) Only dry sample is allowed:






Phase Plate


MEMs fabrication

Bottlenecks for Biological Imaging

- a) Lack of contrast: Zernike Phase Plate

 (alternate the phase of electron wave in focal plane)
- b) Only dry sample is allowed: Wet Cell






NTHU





Wet cell: bio-sample in liquid environment








NTHU

Wet cell: bio-sample in liquid environment
















Enhance Phase Contrast

piezo-driven holder








NTHU

Enhance Phase Contrast

piezo-driven holder









Zernike Phase Plate Nobel Prize (1953)



-120 nm





Radostin Danev, Kuniaki Nagayama Ultramicroscopy 88(2001) 243-212





NTHU


Boersch Phase Plate:
Tunable Phase Contrast——— Wave































 $\Delta f=0$, in focus




15nm 12nm


Phase image of gate oxide





Rose Contrast =
$$\frac{1 - 2}{1 - 2} x \frac{(\sigma_1^2 + \sigma_2^2)^{1/2}}{(\sigma_1^2 + \sigma_2^2)^{1/2}}$$


ournal of Electron Microscopy 55: 273-280 (2006)
























Proposed Phase Tomography in TEM



Phase Tomography

Phase Problems Conclusions

- Diffractive Imaging (recover the phase in diffraction plane)
- Recover the phase in the real space (TIE)
- Aberration Correction/ Exit Wave Reconstruction
- Focal plate: determination of the geometry of exit surface of sample
- Phase Plate: Alternating the phase to improve the contrast for biological sample


Conclusion


- (a) Stable Boesch Phase Plate (Einzel lens) under electron beam (no damage and no charge)
- (b) New design of Phase plate and integration with the electron optics of TEM is being carried out to improve the phase efficiency and reducing the absorption effect
- (c) Alignment of optical axes of Phase Plate and Objective lens




Wet Cell Fabricated by MEMS


(without modification of TEM)





sealing of wet cell





Au particle in water Au particles in Glycerol